

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1 Product identifier**arecal Fillup Ultra
Article number: 089662010**1.2 Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Relevant uses**

Lubricant

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company	Kellner & Kunz AG Boschstr. 37 4600 Wels / AUSTRIA Phone 0043-7242-484-0 Fax 0043-7242-484-924 Homepage www.reca.co.at E-mail info@reca.co.at
----------------	---

Address enquiries to

Technical information	info@reca.co.at
Safety Data Sheet	sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body	+43 (0) 1 406 43 43 (24h)
----------------------	---------------------------

SECTION 2: Hazards identification**2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]**

Flam. Liq. 3: H226 Flammable liquid and vapour.
 Asp. Tox. 1: H304 May be fatal if swallowed and enters airways.
 STOT SE 3: H336 May cause drowsiness or dizziness.
 STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure.
 Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms**Signal word**

DANGER

Contains:Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)**Hazard statements**H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H336 May cause drowsiness or dizziness.
H372 Causes damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.**Precautionary statements**P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P271 Use only outdoors or in a well-ventilated area.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER / doctor.
P331 Do NOT induce vomiting.
P403+P235 Store in a well-ventilated place. Keep cool.**Special labelling**

EUH066 Repeated exposure may cause skin dryness or cracking.



2.3 Other hazards

Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	none

SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

Range [%]	Substance
50 - <75	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics EINECS/ELINCS: 927-241-2, Reg-No.: 01-2119471843-32-XXXX GHS/CLP: Flam. Liq. 3: H226 - Asp. Tox. 1: H304 - STOT SE 3: H336 - Aquatic Chronic 3: H412
10 - <20	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) CAS: 1174522-09-8, EINECS/ELINCS: 919-164-8, Reg-No.: 01-2119473977-17-XXXX GHS/CLP: Asp. Tox. 1: H304 - Aquatic Chronic 3: H412 - STOT RE 1: H372
0,1 - <1	Benzenesulfonic acid, di-C10-14 alkyl derivs., calcium salts CAS: 1471316-72-9, EINECS/ELINCS: 939-603-7, Reg-No.: 01-2119978241-36-XXXX GHS/CLP: Skin Sens. 1: H317

Comment on component parts	Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%. For full text of H-statements: see SECTION 16.
----------------------------	---

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Get medical advice. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Headache
Allergic reactions

4.3 Indication of any immediate medical attention and special treatment needed

If swallowed or in the event of vomiting, risk of product entering the lungs.
Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

Risk of formation of toxic pyrolysis products.
In the event of fire the following can be released:
Not combusted hydrocarbons.
Carbon monoxide (CO)



5.3 Advice for firefighters

Use self-contained breathing apparatus.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
High risk of slipping due to leakage/spillage of product.
Use breathing apparatus if exposed to vapours/dust/aerosol.

6.2 Environmental precautions

Prevent spread over a wide area (e.g. by containment or oil barriers).
Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up with absorbent material (e.g. acid binder).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provide good room ventilation even at ground level (vapours are heavier than air).
Use solvent-resistant equipment.
Keep away from all sources of ignition - Refrain from smoking.
Take precautionary measures against static discharges.
Vapours can form an explosive mixture with air.
Do not eat, drink, smoke or take drugs at work.
Remove soiled or soaked clothing immediately.
Wash hands before breaks and after work.
Use barrier skin cream.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Keep only in original container.
Prevent penetration into the ground.
Provide floor with bunding.
Do not store together with oxidizing agents.
Protect from heat/overheating.
Keep container in a well-ventilated place.
Keep container tightly closed.

7.3 Specific end use(s)

See product use, SECTION 1.2



SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
EINECS/ELINCS: 927-241-2, Reg-No.: 01-2119471843-32-XXXX
Long-term exposure: 100 ppm, 525 mg/m ³ , OSHA
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
CAS: 1174522-09-8, EINECS/ELINCS: 919-164-8, Reg-No.: 01-2119473977-17-XXXX
Long-term exposure: 500 mg/m ³

DNEL

Substance
Benzenesulfonic acid, di-C10-14 alkyl derivs., calcium salts
Industrial, dermal, Long-term - systemic effects: 25 mg/kg bw/day.
Industrial, inhalative, Long-term - systemic effects: 35,26 mg/m ³ .
general population, oral, Long-term - systemic effects: 2,5 mg/kg bw/day.
general population, dermal, Long-term - systemic effects: 12.5 mg/kg bw/day.
general population, inhalative, Long-term - systemic effects: 8,7 mg/m ³ .
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
Industrial, dermal, Long-term - systemic effects: 208 mg/kg bw/day.
Industrial, inhalative, Long-term - systemic effects: 871 mg/m ³ .
general population, inhalative, Long-term - systemic effects: 185 mg/m ³ .
general population, dermal, Long-term - systemic effects: 125 mg/kg bw/day.
general population, oral, Long-term - systemic effects: 125 mg/kg bw/day.

PNEC

Substance
Benzenesulfonic acid, di-C10-14 alkyl derivs., calcium salts
soil, 36739,74 mg/kg soil dw.
sediment (seawater), 45211 mg/kg sediment dw.
sediment (freshwater), 45211 mg/kg sediment dw.
sewage treatment plants (STP), 1000 mg/l.
seawater, 0,1 mg/l.
freshwater, 0,1 mg/l.



8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. 0,7 mm Butyl rubber, >480 min (EN 374-1/-2/-3).
Skin protection	Solvent-resistant protective clothing (EN 340)
Other	Do not inhale gases/vapours/aerosols. Avoid contact with eyes and skin. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: filter apparatus, filter A. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	liquid
Color	light brown
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	> 100
Flash point [°C]	24 (ISO 3679)
Flammability (solid, gas) [°C]	No information available.
Lower explosion limit	0,6 Vol.-%
Upper explosion limit	7 Vol.-%
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	< 110 [50°C]
Density [g/ml]	0,795 (DIN 51757) (20 °C / 68,0 °F)
Bulk density [kg/m³]	not applicable
Solubility in water	insoluble
Partition coefficient [n-octanol/water]	No information available.
Viscosity	< 20,5 mm²/s (40°C)
Relative vapour density determined in air	No information available.
Evaporation speed	No information available.
Melting point [°C]	No information available.
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not applicable

9.2 Other information

none



SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.
Reactions with strong oxidizing agents.

10.4 Conditions to avoid

See SECTION 7.2.

10.5 Incompatible materials

Strong oxidizing agent.

10.6 Hazardous decomposition products

Flammable gases/vapours.



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled.:
oral, Based on the available information, the classification criteria are not fulfilled.:
dermal, Based on the available information, the classification criteria are not fulfilled.:
Substance
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), CAS: 64742-82-1
LD50, dermal, Rabbit: >2000 mg/kg (OECD 402).
LD50, oral, Rat: >5000 mg/kg (OECD 401).
LC50, inhalative, Rat: >13.1 mg/l (4h) (OECD 403).
Benzenesulfonic acid, di-C10-14 alkyl derivs., calcium salts
LD50, dermal, Rabbit: >2000 mg/kg bw (OECD 402) >1.9 mg/l air (EPA OPP .
LD50, oral, Rat: >10000 - <20000 mg/kg bw (Lit.).
LC50, inhalative, Rat: >1,9 mg/l air (EPA OPP 81-3) >1.9 mg/l air (EPA O.
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
LD50, dermal, Rabbit: > 5000 mg/kg (OECD 402).
LD50, oral, Rat: > 5000 mg/kg (OECD 401).
LC50, inhalative, Rat: > 4951 mg/m ³ (OECD 403).

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled.
Skin corrosion/irritation	Based on the available information, the classification criteria are not fulfilled.
Respiratory or skin sensitisation	Based on the available information, the classification criteria are not fulfilled. Classification was carried out based on substance-specific concentration limits. EC 939-603-7 (Skin Sens. 1B: 10%<C<100%) Calculation method
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are fulfilled. Vapours may cause drowsiness and dizziness. Calculation method
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are fulfilled. Causes damage to organs through prolonged or repeated exposure. Calculation method
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	v < 20,5 mm ² /s (40°C) Based on the available information, the classification criteria are fulfilled. May be fatal if swallowed and enters airways.
General remarks	Frequent persistent contact with the skin can cause skin irritation. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials. Toxicological data of complete product are not available.



SECTION 12: Ecological information

12.1 Toxicity

Substance
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%), CAS: 64742-82-1
EL50, (72h), Pseudokirchneriella subcapitata: 10-100 mg/l.
EL50, (48h), Daphnia magna: 10-22 mg/l.
NOEC, (21d), Daphnia magna: 0.097 mg/l.
NOELR, (72h), Pseudokirchneriella subcapitata: 3 mg/l.
LL50, (96h), Oncorhynchus mykiss: 10-100 mg/l.
LOEC, (21d), Daphnia magna: 0.203 mg/l.
Benzenesulfonic acid, di-C10-14 alkyl derivs., calcium salts
EL50, (72h), Scenedesmus subspicatus: >100 mg/l (OECD 201).
EL50, (48h), Daphnia magna: >100 mg/l (OECD 202).
LL50, (96h), Oncorhynchus mykiss: >100 mg/l (OECD 203).
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, < 2% aromatics
EL50, (72h), Pseudokirchneriella subcapitata: > 1000 mg/l.
EL50, (48h), Daphnia magna: 22 - 46 mg/l.
NOELR, (72h), Pseudokirchneriella subcapitata: < 1 mg/l.
LL50, (96h), Oncorhynchus mykiss: 10 - 30 mg/l.

12.2 Persistence and degradability

Behaviour in environment compartments	No information available.
Behaviour in sewage plant	No information available.
Biological degradability	No information available.

12.3 Bioaccumulative potential

No information available.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecotoxicological data are not available.

The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

Do not discharge product unmonitored into the environment.



SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.
Coordinate disposal with the disposal contractor/authorities if necessary.

Waste no. (recommended) 070704*

Contaminated packaging

Uncontaminated packaging may be taken for recycling.
Packaging that cannot be cleaned should be disposed of as for product.

Waste no. (recommended) 150110*

SECTION 14: Transport information

14.1 UN number

Transport by land according to ADR/RID 3295

Inland navigation (ADN) 3295

Marine transport in accordance with IMDG 3295

Air transport in accordance with IATA 3295

14.2 UN proper shipping name

Transport by land according to ADR/RID Hydrocarbons, liquid, n.o.s.

- Classification Code F1

- Label



- ADR LQ 5 I

- ADR 1.1.3.6 (8.6) Transport category (tunnel restriction code) 3 (E)

Inland navigation (ADN) Hydrocarbons, liquid, n.o.s.

- Classification Code F1

- Label



Marine transport in accordance with IMDG Hydrocarbons, liquid, n.o.s.

- EMS F-E, S-D

- Label



- IMDG LQ 5 I

Air transport in accordance with IATA Hydrocarbons, liquid, n.o.s.

- Label



**14.3 Transport hazard class(es)**

Transport by land according to ADR/RID 3

Inland navigation (ADN) 3

Marine transport in accordance with IMDG 3

Air transport in accordance with IATA 3

14.4 Packing group

Transport by land according to ADR/RID III

Inland navigation (ADN) III

Marine transport in accordance with IMDG III

Air transport in accordance with IATA III

14.5 Environmental hazards

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

No information available.

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS 1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014

TRANSPORT-REGULATIONS ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)

NATIONAL REGULATIONS (GB): EH40/2005 Workplace exposure limits (Second edition, published December 2011).

- **Observe employment restrictions for people** Observe employment restrictions for young people.
Observe employment restrictions for mothers-to-be and nursing mothers.

- **VOC (2010/75/CE)** 70%

15.2 Chemical safety assessment

not applicable

**SECTION 16: Other information****16.1 Hazard statements
(SECTION 03)**

H372 Causes damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
 H412 Harmful to aquatic life with long lasting effects.
 H336 May cause drowsiness or dizziness.
 H304 May be fatal if swallowed and enters airways.
 H226 Flammable liquid and vapour.
 H317 May cause an allergic skin reaction.

16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@/TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information**Classification procedure**

Flam. Liq. 3: H226 Flammable liquid and vapour. (On basis of test data)
 Asp. Tox. 1: H304 May be fatal if swallowed and enters airways. (On basis of test data)
 STOT SE 3: H336 May cause drowsiness or dizziness. (Calculation method)
 STOT RE 1: H372 Causes damage to organs through prolonged or repeated exposure. (Calculation method)
 Aquatic Chronic 3: H412 Harmful to aquatic life with long lasting effects. (Calculation method)

Modified position

SECTION 2 been added: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)
 SECTION 8 been added: In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection.
 SECTION 8 deleted: Respiratory protection mask in the event of high concentrations.
 SECTION 11 been added: Classification was carried out based on substance-specific concentration limits.
 SECTION 11 deleted: May produce an allergic reaction.



Copyright: Chemiebüro®