


SECTION 1: Identification of the substance/mixture and of the company/undertaking
1.1 Product identifier

S25 Pistolenreiniger
Article number: 0898225

1.2 Relevant identified uses of the substance or mixture and uses advised against
1.2.1 Relevant uses

For removal of fresh PU foam.

1.2.2 Uses advised against

None known.

1.3 Details of the supplier of the safety data sheet

Company Kellner & Kunz AG
 Boschstr. 37
 4600 Wels / AUSTRIA
 Phone 0043-7242-484-0
 Fax 0043-7242-484-924
 Homepage www.reca.co.at
 E-mail info@reca.co.at

Address enquiries to

Technical information info@reca.co.at
Safety Data Sheet sdb@chemiebuero.de

1.4 Emergency telephone number

Advisory body +43 (0) 1 406 43 43 (24h)

SECTION 2: Hazards identification
2.1 Classification of the substance or mixture [REGULATION (EC) No 1272/2008]

Aerosol 1: H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated.
 Eye Irrit. 2: H319 Causes serious eye irritation.
 STOT SE 3: H336 May cause drowsiness or dizziness.

2.2 Label elements

The product is required to be labelled in accordance with regulation (EC) No 1272/2008 (CLP).

Hazard pictograms

Signal word

DANGER

Contains:

Acetone

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: May burst if heated.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C / 122°F.
 P261 Avoid breathing vapours / spray.
 P271 Use only outdoors or in a well-ventilated area.
 P280 Wear eye protection / face protection.

Special labelling

EUH066 Repeated exposure may cause skin dryness or cracking.

Cleaner, 648/2004/CE, contains:

>=30% aliphatic hydrocarbons (propellant)



2.3 Other hazards

Physico-chemical hazards	Heat causes increase in pressure and risk of bursting.
Environmental hazards	Does not contain any PBT or vPvB substances.
Other hazards	none

SECTION 3: Composition / Information on ingredients

Product-type:

3.2 The product is a mixture.

Range [%]	Substance
>25	Acetone CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX GHS/CLP: Flam. Liq. 2: H225 - Eye Irrit. 2: H319 - STOT SE 3: H336
25 - <50	Butane CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280
25 - <50	Propane CAS: 74-98-6, EINECS/ELINCS: 200-827-9, EU-INDEX: 601-003-00-5, Reg-No.: 01-2119486944-21-XXXX GHS/CLP: Flam. Gas 1: H220 - Press. Gas: H280

Comment on component parts Substances of Very High Concern - SVHC: substances are not contained or are below 0.1%.
For full text of H-statements: see SECTION 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information	Take off contaminated clothing and wash before reuse.
Inhalation	Ensure supply of fresh air. In the event of symptoms seek medical treatment.
Skin contact	When in contact with the skin, clean with soap and water. Consult a doctor if skin irritation persists.
Eye contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Ingestion	Seek medical advice immediately. Do not induce vomiting. Rinse out mouth and give plenty of water to drink.

4.2 Most important symptoms and effects, both acute and delayed

Headache

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media	Foam, dry powder, water spray jet, carbon dioxide.
Extinguishing media that must not be used	Full water jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire the following can be released:
Carbon monoxide (CO)
Not combusted hydrocarbons.
Bursting aerosols can be forcibly projected from a fire.



5.3 Advice for firefighters

Use self-contained breathing apparatus.
Cool containers at risk with water spray jet.
Fire residues and contaminated firefighting water must be disposed of in accordance within the local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep away from all sources of ignition.
Ensure adequate ventilation.
Use personal protective equipment.

6.2 Environmental precautions

Do not discharge into the drains/surface waters/groundwater.

6.3 Methods and material for containment and cleaning up

Take up mechanically.
Take up residues with absorbent material (e.g. sand, sawdust, general purpose binder, diatomaceous earth).
Dispose of absorbed material in accordance within the regulations.

6.4 Reference to other sections

See SECTION 8+13

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Use only in well-ventilated areas.
Use solvent-resistant equipment.
Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.
Vapours/spray can form an explosive mixture with air.
Use explosion-proofed equipment/fittings and non-sparkling tools.
Take precautionary measures against static discharges.
Do not smoke when working.
Wash hands before breaks and after work.
Use barrier skin cream.
Take off contaminated clothing and wash before reuse.

7.2 Conditions for safe storage, including any incompatibilities

Provide solvent-resistant and impermeable floor.
Prevent penetration into the ground.
Do not store together with oxidizing agents.
Keep in a cool place, heat causes increase in pressure and risk of bursting.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C.
Keep container in a well-ventilated place.

7.3 Specific end use(s)

See product use, SECTION 1.2



SECTION 8: Exposure controls / personal protection

8.1 Control parameters

Ingredients with occupational exposure limits to be monitored (GB)

Substance
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
Long-term exposure: 500 ppm, 1210 mg/m ³
Short-term exposure (15-minute): 1500 ppm, 3620 mg/m ³
Butane
CAS: 106-97-8, EINECS/ELINCS: 203-448-7, EU-INDEX: 601-004-00-0, Reg-No.: 01-2119474691-32-XXXX
Long-term exposure: 600 ppm, 1450 mg/m ³
Short-term exposure (15-minute): 750 ppm, 1810 mg/m ³

Ingredients with occupational exposure limits to be monitored (EU)

Substance / EC LIMIT VALUES
Acetone
CAS: 67-64-1, EINECS/ELINCS: 200-662-2, EU-INDEX: 606-001-00-8, Reg-No.: 01-2119471330-49-XXXX
Eight hours: 500 ppm, 1210 mg/m ³

DNEL

Substance
Acetone, CAS: 67-64-1
Industrial, dermal, Long-term - systemic effects: 186 mg/kg bw/d.
Industrial, inhalative, Long-term - systemic effects: 1210 mg/m ³ .
Industrial, inhalative, Long-term - local effects: 2420 mg/m ³ .
general population, inhalative, Long-term - systemic effects: 200 mg/m ³ .
general population, oral, Long-term - systemic effects: 62 mg/kg bw/d.
general population, dermal, Long-term - systemic effects: 62 mg/kg bw/d.

PNEC

Substance
Acetone, CAS: 67-64-1
sewage treatment plants (STP), 100 mg/L.
soil, 29,5 mg/kg soil dw.
sediment (seawater), 3,04 mg/kg sediment dw.
sediment (freshwater), 30,4 mg/kg sediment dw.
seawater, 1,06 mg/L.
freshwater, 10,6 mg/L.



8.2 Exposure controls

Additional advice on system design	Ensure adequate ventilation on workstation. Measurement methods for taking workplace measurements must meet the performance requirements of DIN EN 482. For example, recommendations are given in the IFA's list of hazardous substances.
Eye protection	Safety glasses. (EN 166:2001)
Hand protection	The details concerned are recommendations. Please contact the glove supplier for further information. 0,7 mm Butyl rubber, >480 min (EN 374-1/-2/-3).
Skin protection	light protective clothing
Other	Do not inhale aerosols. Avoid contact with eyes and skin. Personal protective equipment should be selected specifically for the working place, depending on concentration and quantity handled. The resistance of this equipment to chemicals should be ascertained with the respective supplier.
Respiratory protection	In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection. Short term: combination filter AX-P2. (DIN EN 14387)
Thermal hazards	No information available.
Delimitation and monitoring of the environmental exposition	Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Form	aerosol
Color	colourless
Odor	characteristic
Odour threshold	No information available.
pH-value	not applicable
pH-value [1%]	not applicable
Boiling point [°C]	not applicable
Flash point [°C]	not applicable
Flammability (solid, gas) [°C]	not applicable
Lower explosion limit	1,8 Vol.-%
Upper explosion limit	13 Vol.-%
Oxidising properties	no
Vapour pressure/gas pressure [kPa]	853 (20 °C)
Density [g/ml]	No information available.
Bulk density [kg/m³]	not applicable
Solubility in water	soluble
Partition coefficient [n-octanol/water]	No information available.
Viscosity	not applicable
Relative vapour density determined in air	not applicable
Evaporation speed	not applicable
Melting point [°C]	not applicable
Autoignition temperature [°C]	not applicable
Decomposition temperature [°C]	not applicable

9.2 Other information

none



SECTION 10: Stability and reactivity

10.1 Reactivity

See SECTION 10.3.

10.2 Chemical stability

Stable under normal ambient conditions (ambient temperature).

10.3 Possibility of hazardous reactions

Evolution of flammable mixtures possible in air when heated above flash point and/or during spraying or misting.
Risk of bursting.

10.4 Conditions to avoid

Strong heating.
See SECTION 7.2.

10.5 Incompatible materials

No information available.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product
inhalative, Based on the available information, the classification criteria are not fulfilled.:
dermal, Based on the available information, the classification criteria are not fulfilled.:
oral, Based on the available information, the classification criteria are not fulfilled.:
Substance
Propane, CAS: 74-98-6
LC50, inhalative, Rat: > 1443 mg/l (15 min) (Lit.).
Butane, CAS: 106-97-8
LC50, inhalative, Rat: 658 mg/l (4 h) (Lit.).
Acetone, CAS: 67-64-1
LD50, dermal, Rabbit: > 15800 mg/kg.
LD50, oral, Rat: 5800 mg/kg (OECD 401).
LC50, inhalative, Rat: 76 mg/l (4h).

Serious eye damage/irritation	Based on the available information, the classification criteria are not fulfilled. Based on the available information, the classification criteria are fulfilled. Irritant Calculation method [RL (EC) No. 1272/2008 Annex I 1.1.3.7]
Skin corrosion/irritation	Based on the available information, the classification criteria are not fulfilled.
Respiratory or skin sensitisation	Based on the available information, the classification criteria are not fulfilled.
Specific target organ toxicity — single exposure	Based on the available information, the classification criteria are not fulfilled. Based on the available information, the classification criteria are fulfilled. Vapours may cause drowsiness and dizziness. Calculation method [RL (EC) No. 1272/2008 Annex I 1.1.3.7]
Specific target organ toxicity — repeated exposure	Based on the available information, the classification criteria are not fulfilled.
Mutagenicity	Based on the available information, the classification criteria are not fulfilled.
Reproduction toxicity	Based on the available information, the classification criteria are not fulfilled.
Carcinogenicity	Based on the available information, the classification criteria are not fulfilled.
Aspiration hazard	Based on the available information, the classification criteria are not fulfilled.
General remarks	Frequent persistent contact with the skin can cause skin irritation. Toxicological data of complete product are not available. The toxicity data listed pertaining to the ingredients are intended for those working in the medicinal professions, experts for occupational health and safety and toxicologists. The toxicity data pertaining to the ingredients were supplied by the manufacturers of raw materials.

SECTION 12: Ecological information

12.1 Toxicity

Product
Based on the available information, the classification criteria are not fulfilled.:
Substance
Acetone, CAS: 67-64-1
LC50, (48h), Daphnia pulex: 8800 mg/l.
LC50, (96h), Oncorhynchus mykiss: 5540 mg/l.
NOEC, (28d), Daphnia magna: 2212 mg/l.
NOEC, (96h), Algae: 430 mg/l.



12.2 Persistence and degradability

Behaviour in environment compartments	No information available.
Behaviour in sewage plant	No information available.
Biological degradability	The product is readily biodegradable.

12.3 Bioaccumulative potential

Accumulation in organisms is not expected.

12.4 Mobility in soil

No information available.

12.5 Results of PBT and vPvB assessment

Based on all available information not to be classified as PBT or vPvB respectively.

12.6 Other adverse effects

Ecological data of complete product are not available.
Do not discharge product unmonitored into the environment.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste material c It is not possible to determine a waste code for this product in accordance with the European Waste Catalogue (EWC) since it is only possible to classify it according to how it is used by the customer. The waste code is to be determined within the EU in liaison with the waste-disposal operator.

Product

Dispose of as hazardous waste.
Coordinate disposal with the authorities if necessary.

Waste no. (recommended)

160504* gases in pressure containers (including halons) containing dangerous substances

Contaminated packaging

Untaminated packaging may be taken for recycling.
Dispose full / partially emptied cartridges as hazardous waste in accordance with official regulations.

Waste no. (recommended)

150110*

SECTION 14: Transport information

14.1 UN number


Transport by land according to ADR/RID 1950


Inland navigation (ADN) 1950


Marine transport in accordance with IMDG 1950


Air transport in accordance with IATA 1950

**14.2 UN proper shipping name**

Transport by land according to ADR/RID	Aerosols
- Classification Code	5F
- Label	
- ADR LQ	1 I
- ADR 1.1.3.6 (8.6)	Transport category (tunnel restriction code) 2 (D)

Inland navigation (ADN)	Aerosols
- Classification Code	5F
- Label	

Marine transport in accordance with IMDG	Aerosols
- EMS	F-D, S-U
- Label	
- IMDG LQ	1 I

Air transport in accordance with IATA	Aerosols, flammable
- Label	

14.3 Transport hazard class(es)

Transport by land according to ADR/RID	2
Inland navigation (ADN)	2
Marine transport in accordance with IMDG	2.1
Air transport in accordance with IATA	2.1

14.4 Packing group

Transport by land according to ADR/RID	not applicable
Inland navigation (ADN)	not applicable
Marine transport in accordance with IMDG	not applicable
Air transport in accordance with IATA	not applicable

**14.5 Environmental hazards**

Transport by land according to ADR/RID no

Inland navigation (ADN) no

Marine transport in accordance with IMDG no

Air transport in accordance with IATA no

14.6 Special precautions for user

Relevant information under SECTION 6 to 8.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

not determined

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

EEC-REGULATIONS	1991/689 (2001/118); 2010/75; 2004/42; 648/2004; 1907/2006 (REACH); 1272/2008; 75/324/EEC (2016/2037/EC); (EU) 2015/830; (EU) 2016/131; (EU) 517/2014
TRANSPORT-REGULATIONS	ADR (2019); IMDG-Code (2019, 39. Amdt.); IATA-DGR (2019)
NATIONAL REGULATIONS (GB):	EH40/2005 Workplace exposure limits (Second edition, published December 2011).
- Observe employment restrictions for people	Observe employment restrictions for young people. GENERAL REVIEW
- VOC (2010/75/CE)	100%

15.2 Chemical safety assessment

not applicable

SECTION 16: Other information**16.1 Hazard statements (SECTION 03)**

H280 Contains gas under pressure; may explode if heated.
H220 Extremely flammable gas.
H336 May cause drowsiness or dizziness.
H319 Causes serious eye irritation.
H225 Highly flammable liquid and vapour.



16.2 Abbreviations and acronyms:

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
 RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
 ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
 ATE = acute toxicity estimate
 CAS = Chemical Abstracts Service
 CLP = Classification, Labelling and Packaging
 DMEL = Derived Minimum Effect Level
 DNEL = Derived No Effect Level
 EC50 = Median effective concentration
 ECB = European Chemicals Bureau
 EEC = European Economic Community
 EINECS = European Inventory of Existing Commercial Chemical Substances
 ELINCS = European List of Notified Chemical Substances
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals
 IATA = International Air Transport Association
 IBC-Code = International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
 IC50 = Inhibition concentration, 50%
 IMDG = International Maritime Code for Dangerous Goods
 IUCLID = International Uniform Chemical Information Database
 LC50 = Lethal concentration, 50%
 LD50 = Median lethal dose
 LC0 = lethal concentration, 0%
 LOAEL = lowest-observed-adverse-effect level
 MARPOL = International Convention for the Prevention of Marine Pollution from Ships
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 PBT = Persistent, Bioaccumulative and Toxic substance
 PNEC = Predicted No-Effect Concentration
 REACH = Registration, Evaluation, Authorisation and Restriction of Chemicals
 STP = Sewage Treatment Plant
 TLV@/TWA = Threshold limit value – time-weighted average
 TLV@STEL = Threshold limit value – short-time exposure limit
 VOC = Volatile Organic Compounds
 vPvB = very Persistent and very Bioaccumulative

16.3 Other information

Customs Tariff

38140090

Classification procedure

Aerosol 1: H222 Extremely flammable aerosol. (Bridging principle "Aerosols") H229 Pressurised container: May burst if heated. (Bridging principle "Aerosols")
 Eye Irrit. 2: H319 Causes serious eye irritation. (Calculation method [RL (EC) No. 1272/2008 Annex I 1.1.3.7])
 STOT SE 3: H336 May cause drowsiness or dizziness. ()

Modified position

SECTION 8 been added: In the event of occupational exposure limits being exceeded or of inadequate ventilation: wear appropriate respiratory protection.
 SECTION 8 deleted: Respiratory protection mask in the event of high concentrations.

Copyright: Chemiebüro®